



**LASER SHOT  
LBP 6000**

**Canon**

Compact, energy-efficient desktop monochrome laser printer. Delivering quality, maintenance-free prints, this energy-saving device is easy to use and exceptionally quiet.



**19 ppm  
laser printing**

**First Print Out  
in 7.8 Seconds**

**600 x 600 dpi  
print resolution**

**Space-Saving  
Design**

**Energy Efficient**

**Quiet Operation**

## Key Features

- Productive 19ppm (LTR) mono laser printing
- Quick warm-up time from sleep mode
- First Print Out Time of only 7.8 seconds or less
- Up to 2400 x 600 dpi resolution for high quality prints with Automatic Image Refinement
- Highly efficient 1.3W power consumption in sleep mode
- Quiet operation and inaudible in StandBy mode
- Convenient, easy to use All-in-One cartridge

# Specifications

## PRINTER ENGINE

Print speed:	Up to 19ppm mono (LTR)
Printing method:	Black and White Laser beam printing
Fixing method:	On Demand Fixing
Print Quality:	Up to 2400x600 dpi with Automatic Image Refinement
Print resolution:	Up to 600x600 dpi
Warm-up time:	10 seconds or less
First Page Out Time:	7.8 seconds or less
Duty Cycle:	Max. 5,000 pages per month
Print Margins:	5 mm-top, bottom, left and right

## MEDIA HANDLING

Paper input (Standard):	150-sheet multi-purpose tray
Paper output:	100-sheet face down
Media types:	Plain paper, Heavy paper, Transparency, Label, Envelope
Media sizes:	Standard: A4, B5, A5, Legal, Letter, Executive, 16K, Custom sizes: COM10/Monarch/C5/DL/ISO-B5 width 76.2 to 215.9mm; Length 188 to 355.6mm
Media weights:	Multi-purpose tray: 60 to 163 g/m <sup>2</sup>

## GENERAL FEATURES

Power Requierments:	AC 110-127V (±10%) 50/60 Hz (±2Hz) AC 220-240V (±10%) 50/60 Hz (±2Hz)
Power consumption:	Maximum (120V): 850W or less Maximum (220V): 910W or less Active (120-127V): Average approx. 310W Active (220-240V): Average approx. 295W Standby: Average approx. 1.6W Typical Electricity Consumption (TEC): 0.5 kWh/week
Noise level:	Sound power: Active: 6.34 B or less Standby: Inaudible Sound pressure: Active: 50 dB(A) Standby: Inaudible
Dimensions (W x D x H):	359mm x 249mm x 190mm
Weight:	Approx. 5.0 kg
Operating environment:	Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation)
Control panel:	1 LED indicators 1 operation key

## CONTROLLER

Buffer/RAM:	2MB buffer memory
Printer languages:	CAPT 3.0 (Canon Advanced Printing Techonology)
Compression:	Hi-SCoA (Canon's High Smart Compression Architecture)
Interface and Connectivity:	USB 2.0 High-speed
Operating Systems:	Windows 7(32/64bit)/Windows Vista(32/64bit)/XP(32/64bit) Server 2008 (32/64bit)/Server 2008 R2(32/64bit) 2003 server(32/64bit)/2000 Mac OS X 10.4.9 - 10.6.X, Linux (online distribution only)

## CONSUMABLES

Toner cartridges:	Starter: Cartridge 125 Black (700 pages <sup>1</sup> ) <sup>2</sup> Standard: Cartridge 125 Black (1,600 pages <sup>1</sup> )
-------------------	--

<sup>1</sup> Based on ISO/IEC 19752

<sup>2</sup> Printer ships with CRG 125 Black (700 pages) toner cartridge



[www.cla.canon.com](http://www.cla.canon.com)

Canon Latin America, Inc.  
703 Waterford Way  
Suite 400  
Miami, FL 33126

LASER SHOT and CANON are registered trademarks of Canon Inc. in the United States and may also be a registered trademark or trademark in other countries. Specifications and availability subject to change without notice.  
©2010 Canon Latin America, Inc. All rights reserved.